

Package ‘updateme’

March 14, 2024

Type Package

Title Informative Messages About Outdated Packages

Version 0.1.0

Description When a package is loaded, the source repository is checked for new versions and a message is shown in the console indicating whether the package is out of date.

License MIT + file LICENSE

Encoding UTF-8

URL <https://github.com/wurli/updateme>,
<https://wurli.github.io/updateme/>

BugReports <https://github.com/wurli/updateme/issues>

Imports cachem, cli (>= 3.6.0), curl, memoise, rlang, utils

RoxygenNote 7.2.3

Suggests BiocManager, gitcreds, knitr, rmarkdown, testthat (>= 3.0.0),
withr

Config/testthat/edition 3

NeedsCompilation no

Author Jacob Scott [aut, cre]

Maintainer Jacob Scott <jscott2718@gmail.com>

Repository CRAN

Date/Publication 2024-03-14 20:10:02 UTC

R topics documented:

updateme_on	2
updateme_sources_set	2

Index	5
--------------	----------

update_me_on	<i>Temporarily turn update_me off for all packages</i>
--------------	--

Description

These functions may be useful if you find the slight delay caused by update_me looking up new package versions to be slowing down your workflow.

Usage

```
update_me_on()
```

```
update_me_off()
```

Value

The old update_me.on option, as returned by options()

See Also

[update_me_sources_set\(\)](#) to turn update_me off for individual packages

update_me_sources_set	<i>Configure update_me lookup of new package versions</i>
-----------------------	---

Description

This function is a helper for setting the "update_me.sources" global option. It provides a user-friendly interface and validation of the options you set.

Usage

```
update_me_sources_set(...)
```

Arguments

- ...
- Named or unnamed arguments. Values should be either:
- One of names(getOption("repo")): latest versions will be taken from this source, if available
 - "bioc": new versions will be looked for on Bioconductor
 - "github"/"gitlab": new versions will be looked for on GitHub/GitLab, if a repo can be identified using the package DESCRIPTION
 - A URL pointing to a GitHub/GitLab repo, e.g. "https://github.com/wurli/update_me": the latest version *for this particular package* will be taken from this project

- NA: update_me will not attempt to query new versions. Note that NA inputs must always be named (i.e. you must specify this 'per package')
- NULL: return to the default behaviour

If arguments are named, names should indicate package which the option should apply to. If unnamed, the option will apply to all packages. See examples for more information.

Value

The result of setting options(update_me.sources = <new_options>)

Private Repositories

update_me supports packages installed from private repositories on GitHub and GitLab. To get upstream package version from either, you should only have to configure a personal access token (PAT):

- For GitHub packages, update_me checks, in order:
 - The GITHUB_PAT environmental variable
 - The GITHUB_TOKEN environmental variable
 - Any personal access tokens configured using `gitcreds::gitcreds_set()`
- For GitLab packages, update_me checks, in order:
 - The GITLAB_PAT environmental variable
 - The GITLAB_TOKEN environmental variable
 - Any personal access tokens configured using `gitcreds::gitcreds_set()`

See Also

`update_me_on()` and `update_me_off()` to disable update_me for all packages

Examples

```
# If you want to check non-standard repos for new versions of packages,
# you'll first have to set the repos global option. Note that each
# option must be named for compatibility with update_me
old_repos <- options(repos = c(

  # Your default CRAN mirror will likely be something like this
  CRAN = "https://cloud.r-project.org",

  # The r-lib r-universe, including dev versions of infrastructure packages
  # like cli, rlang, etc
  `r-lib` = "https://r-lib.r-universe.dev"
))

# 1. New versions will first be looked up from the r-lib R universe by default
# 2. If not found, they will be looked up from the usual CRAN mirror
# 3. dplyr will always be first looked up from GitHub
# 4. ggplot2 won't be looked up or notified about
```

```
old_updateme_sources <- updateme_sources_set(  
  "r-lib",  
  "CRAN",  
  dplyr = "https://github.com/tidyverse/dplyr", # Name is optional here  
  ggplot2 = NA  
)  
  
# memoise should now be looked up from the r-lib r-universe  
if (interactive()) {  
  library(memoise)  
}  
  
# Restore old options  
options(old_repos)  
options(old_updateme_sources)
```

Index

`gitcreds::gitcreds_set()`, [3](#)

`updateme_off (updateme_on)`, [2](#)

`updateme_off()`, [3](#)

`updateme_on`, [2](#)

`updateme_on()`, [3](#)

`updateme_sources_set`, [2](#)

`updateme_sources_set()`, [2](#)